

TECHFLEX

Braided Sleeving Products



FLEXO PET is used in wire harnessing applications where cost efficiency and durability are critical. The product has a wide operating temperature range and is resistant to chemical degradation, UV radiation and abrasion. The wide range of available colors and sizes allows easy and systematic color coding in complex wiring and cabling schemes. The material cuts easily and cleanly with a hot knife and the unique braided construction and wide expansion range allows easy installation over large connectors and long wire runs.

Nominal Diameter	Minimum Diameter	Maximum Diameter	Shop Spool Put Up	Retail Spool Put Up
1/8"	3/32"	1/4"	225'	110'
1/4"	1/8"	7/16"	200'	100'
3/8"	3/16"	5/8"	125'	60'
1/2"	1/4"	3/4"	100'	50'
3/4"	1/2"	1 1/4"	75'	35'
1 1/4"	3/4"	1 3/4"	50'	25'
1 1/2"	1"	2 1/2"	40'	20'
1 3/4"	1 1/4"	2 3/4"	30'	15'
2"	1 1/2"	3 1/2"	50'	14'



By changing the surface characteristics of individual filaments, the engineers at TECHFLEX have produced a product with the same characteristics of our FLEXO PET with the advantage of being able to cut with ordinary scissors and still maintain a fray-resistant end. FLEXO CLEAN CUT (CC) is ideal for field installers and other situations where access to a hot knife is impossible. CC's fray-resistant properties allows frequent expansion at the cut end without unraveling. FLEXO CLEAN CUT is available in both standard polyethylene terephthalate grade (CCN) and as a Flame Retardant product (CCF).



Nominal Diameter	Minimum Diameter	Maximum Diameter	Shop Spool Put Up	Retail Spool Put Up
1/8"	1/8"	1/4"	100'	50'
1/4"	5/32"	7/16"	100'	50'
3/8"	3/16"	5/8"	100'	50'
1/2"	1/4"	3/4"	100'	50'
3/4"	5/8"	1"	75'	40'
1"	3/4"	1 3/16"	50'	25'
1 1/4"	1"	1 1/2"	50'	25'
1 1/2"	1 1/4"	2"	50'	25'



F6N's unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance. The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid configuration simply closes around the installation without the necessity of any secondary sealing technique (velcro, tape, etc.)

Nominal Diameter	Box B Put Up	Bag Put Up
1/8"	100'	25'
1/4"	100'	20'
3/8"	75'	12'
1/2"	75'	10'
3/4"	50'	8'
1"	50'	8'
1 1/2"	25'	4'
2"	25'	4'

