

Fabric

2:1 Fabric Heatshrink Tubing

Shrinks to 1/2 it's original diameter. Fabric heatshrink tubing, a unique mixture of Polyolefin and Polyester yarns, is the ideal way to form the only shrinkable fabric of its kind. The woven construction makes this product extremely flexible and resistant to trapping water, heat and humidity. Provides outstanding abrasion, chafing and cutting protection, even at high temperatures.

Shrinkflex fabric tubing is designed primarily to provide mechanical abrasion protection for components such as rubber hoses, plastic pipes, and harness wiring bundles. Also suitable for other applications, such as noise and rattle suppression.

| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/2" | H2F0.48BK | 12mm | 6mm | 100' | 25' | Black (BK) | 1.15 |
| 3/4" | H2F0.79BK | 20mm | 10mm | 100' | 25' | Black (BK) | 1.61 |
| 1" | H2F0.98BK | 25mm | 12.5mm | 100' | 25' | Black (BK) | 1.71 |
| 1 3/16" | H2F1.18BK | 30mm | 15mm | 100' | 25' | Black (BK) | 2.13 |
| 1 3/8" | H2F1.38BK | 35mm | 17.5mm | 100' | 25' | Black (BK) | 2.35 |
| 1 1/2" | H2F1.58BK | 40mm | 20mm | 100' | 25' | Black (BK) | 2.66 |
| 2" | H2F1.97BK | 50mm | 25mm | 100' | 25' | Black (BK) | 3.44 |
| 2 3/8" | H2F2.36BK | 60mm | 30mm | 100' | 25' | Black (BK) | 4.11 |
| 2 3/4" | H2F2.75BK | 70mm | 35mm | 100' | 25' | Black (BK) | 4.69 |
| 3 1/8" | H2F3.15BK | 80mm | 40mm | 100' | 25' | Black (BK) | 5.29 |

- **Shrink Temp. 176°F**
- **Highly Flexible**
- **Resists Common Automotive Chemicals**
- **Easily Installs Over Connectors & Splices**
- **Halogen Free**



Diesel Resistant

2:1 Diesel Resistant Heatshrink Tubing

Diesel resistant heatshrink tubing is the ideal way to create a tight, professional finish on any wire, hose or cable management project. Once shrunk, the tubing will hold its reduced state even in elevated temperatures. H2D is resistant to aviation and diesel fuels, hydraulic fluids and lubrication oils. It will protect wires, solder joints, terminals, connections and components from most industrial fuels and abrasion.

| Nominal Size | Part # | Unshrunk Diameter | Shrunk Diameter | Standard Spool Put-Ups | | Available Colors | Lbs/100' |
|--------------|-----------|-------------------|-----------------|------------------------|------------|------------------|----------|
| | | | | Bulk Spool | Shop Spool | | |
| 1/8" | H2D0.13BK | 3.2mm | 1.6mm | 500' | 25' | Black (BK) | 0.70 |
| 3/16" | H2D0.19BK | 4.8mm | 2.4mm | 250' | 25' | Black (BK) | 1.00 |
| 1/4" | H2D0.25BK | 6.4mm | 3.2mm | 250' | 25' | Black (BK) | 1.20 |
| 3/8" | H2D0.38BK | 9.6mm | 4.8mm | 200' | 25' | Black (BK) | 1.75 |
| 1/2" | H2D0.50BK | 12.8mm | 6.4mm | 100' | 25' | Black (BK) | 2.75 |
| 3/4" | H2D0.75BK | 19.3mm | 9.5mm | 100' | 25' | Black (BK) | 4.75 |
| 1" | H2D1.00BK | 25.4mm | 12.7mm | 100' | 25' | Black (BK) | 8.80 |
| 1 1/4" | H2D1.25BK | 31.8mm | 15.9mm | 100' | 25' | Black (BK) | |
| 1 1/2" | H2D1.50BK | 38.2mm | 19.1mm | 100' | 25' | Black (BK) | |

- **Shrink Temp. 302°F**
- **Heavy Wall, Flexible Elastomer Polyolefin Tubing**
- **High Resistance to Aviation Fuels, Diesel Fuels and Oils**

*Contact your Account Representative for heatshrink cutting & printing services.

800 323-5140
www.techflex.com